

SPORT PERFORMANCE**DUNLOP SP SPORT A2 PLUS®**H-RATED ALL-SEASON
HIGH-PERFORMANCE TIRE**50,000 MILE TREADLIFE
LIMITED WARRANTY***

FEATURES	BENEFITS
• Non-directional asymmetrical tread pattern	• Responsive handling and all-season performance
• Large, stable, high-density outer tread blocks	• Precise cornering and stability
• Inner tread blocks with more sipes and lateral edges	• Traction on wet, snowy and icy roads
• Three mammoth center ribs and tread grooves	• Straight-line stability and handling
• Enhanced dual phase tread compound	• Longer-lasting tread wear and great traction in water and snow
• Wide water-siphoning grooves	• Excellent wet handling
• High-density steel belts	• Excellent control and long, even tread wear
• Hard rubber bead apex and high ply turn-up	• Confident handling and predictable steering response

SIZE	SERVICE DESC.	LOAD RANGE	SIDE-WALL	PRODUCT CODE	MATERIAL NUMBER	RIM WIDTH (IN)	APPRVD. RIM WIDTHS (IN)	SECTION WIDTH (IN)	OVERALL DIAMETER (IN)	STATIC LOADED RADIUS (IN)	REVS/ MILE	TREAD WIDTH (IN)	TREAD DEPTH (IN)	MAX. LOAD (LBS)	TIRE WEIGHT (LBS)
P195/70R14	90H	SL	BSW	263016270	194235	6.0	5.0 - 6.5	7.9	24.7	11.0	852	5.8	10/32	1323	20.2
P195/65R14	88H	SL	BSW	263016266	194231	6.0	5.5 - 7.0	7.9	23.9	10.7	876	5.9	10/32	1235	19.7
P185/65R14	85H	SL	BSW	263016267	194236	5.5	5.0 - 6.5	7.4	23.4	10.6	894	5.5	10/32	1124	18.8
P175/65R14	81H	SL	BSW	263016265	194170	5.0	5.0 - 6.0	7.0	22.9	10.4	912	5.2	10/32	1019	16.7
P205/60R14	88H	SL	BSW	263016262	194234	6.0	5.5 - 7.5	8.2	23.6	10.7	884	6.4	10/32	1235	20.8
P195/60R14	85H	SL	BSW	263016261	194233	6.0	5.5 - 7.0	7.9	23.1	10.5	901	6.2	10/32	1135	18.8
P185/60R14	82H	SL	BSW	263016260	194232	5.5	5.0 - 6.5	7.4	22.7	10.3	919	5.8	10/32	1047	17.9
P215/65R15	95H	SL	BSW	263016272	194240	6.5	6.0 - 7.5	8.7	25.9	11.6	808	6.5	10/32	1510	22.8
P205/65R15	92H	SL	BSW	263016271	194239	6.0	5.5 - 7.5	8.2	25.4	11.4	823	6.1	10/32	1389	22.3
P195/65R15	89H	SL	BSW	263016269	194238	6.0	5.5 - 7.0	7.9	24.9	11.2	839	5.9	10/32	1235	20.8
P185/65R15	86H	SL	BSW	263016268	194237	5.5	5.0 - 6.5	7.4	24.4	11.1	856	5.5	10/32	1168	18.9
P225/60R15	95H	SL	BSW	263016274	194244	6.5	6.0 - 8.0	9.0	25.5	11.5	817	7.1	10/32	1521	25.8
P215/60R15	93H	SL	BSW	263016273	194243	6.5	6.0 - 7.5	8.7	25.1	11.4	832	6.9	10/32	1411	23.6
P205/60R15	90H	SL	BSW	263016264	194242	6.0	5.5 - 7.5	8.2	24.6	11.2	847	6.4	10/32	1323	21.2
P195/60R15	87H	SL	BSW	263016263	194241	6.0	5.5 - 7.0	7.9	24.1	11.0	862	6.2	10/32	1201	20.6
P205/50R15	84H	SL	BSW	263016250	194245	6.5	5.5 - 7.5	8.4	23.0	10.6	899	7.2	10/32	1102	20.7
P235/60R16	99H	SL	BSW	263016278	194254	7.0	6.5 - 8.5	9.5	27.0	12.2	773	7.4	10/32	1709	27.6
P225/60R16	97H	SL	BSW	263016276	194247	6.5	6.0 - 8.0	9.0	26.5	12.0	786	7.1	10/32	1609	26.9
P215/60R16	94H	SL	BSW	263016275	194246	6.5	6.0 - 7.5	8.7	26.1	11.9	799	6.9	10/32	1477	25.0
P205/60R16	91H	SL	BSW	263016277	194251	6.0	5.5 - 7.5	8.2	25.6	11.7	813	6.4	10/32	1356	22.4
P225/55R16	94H	SL	BSW	263016257	194253	7.0	6.0 - 8.0	9.2	25.6	11.8	809	8.1	10/32	1367	26.4
P215/55R16	91H	SL	BSW	263016256	194252	7.0	6.0 - 7.5	8.9	25.2	11.6	823	7.8	10/32	1356	23.4
P205/55R16	89H	SL	BSW	263016255	194248	6.5	5.5 - 7.5	8.4	24.8	11.4	836	7.4	10/32	1279	22.7
P245/50R16	96H	SL	BSW	263016254	194250	7.5	7.0 - 8.5	9.9	25.5	11.8	811	9.1	10/32	1565	27.3
P225/50R16	91H	SL	BSW	263016253	194249	7.0	6.0 - 8.0	9.2	24.8	11.5	835	8.5	10/32	1367	25.2
P235/55R17	98H	SL	BSW	263016259	194256	7.0	6.0 - 8.0	9.2	26.9	12.3	769	8.1	10/32	1609	27.2
225/55R17	97H	SL	BSW	263016279	194259	7.5	6.5 - 8.5	9.7	27.1	12.4	767	8.5	10/32	1565	28.3
P215/50R17	90H	SL	BSW	263016258	194255	7.0	6.0 - 7.5	8.9	25.4	11.8	814	7.8	10/32	1323	24.9
P215/45R17	87H	SL	BSW	263016245	194258	7.0	7.0 - 8.0	8.4	24.7	11.5	848	7.4	9/32	1201	21.5
P205/40R17	80H	SL	BSW	263016240	194257	7.5	7.0 - 8.0	8.4	23.5	11.1	896	7.1	9/32	992	19.3

UTQG: 460 AA A

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels.



DRIVERS KNOW.®