








## SPORT PERFORMANCE

# DUNLOP SP SPORT MAXX™

PREMIUM LUXURY SPORT TIRE  
WITH COMMANDING POWER

FEATURES	BENEFITS
• Multi Radius Tread Technology  distributes pressure evenly over the contact patch and large footprint	• Delivers superior dry handling without sacrificing wet handling
• Twin Hydro-Paddle Technology  incorporates a directional tread design that rapidly and efficiently drains water out both sides of the tire	• Improves wet handling and deep-water performance
• Integral Rubber Matrix tread compound comprised of an optimized blend of silica and high-structured carbon black	• Demonstrates excellent acceleration and braking performance
• Firm, continuous middle rib efficiently transfers lateral forces	• Gives excellent stability at highway speeds
• 5-Pitch Technology  minimizes subjective and pass-by noise	• Enhances driving comfort
• Jointless Band Technology  , a spiral-wound cap ply technology	• Maintains the tire's structural integrity and enables smooth performance at highway speeds
• Max Flange Shield 	• Protects rims from accidental curb damage

### UNIQUE DUNLOP TECHNOLOGIES



#### **MRT™ Multi-Radius Tread Technology**

This innovative technology distributes pressure evenly over the contact patch for excellent dry traction and handling, without compromising wet performance, through all stages of cornering.



#### **THP™ Twin Hydro-Paddle Technology**

Highly-engineered tread regions efficiently pump water out from under the footprint for responsive handling on wet roads. There are no sipes in this tread design, which means quick, turbulence-free water dispersion.



#### **5-Pitch Technology**

This technology counterbalances vehicle disturbance, as well as minimizes road and pass-by noise. Dunlop computer optimized five different block sizes to break up sound waves and create various frequencies that cancel each other out, so drivers can enjoy a quiet ride.



#### **JLB™ Jointless Band Technology**

It maintains the tire's ideal shape at highway speeds. Nylon is positioned in all the right places to improve handling and tread wear. And unlike sheet cap plies, this one is spiral wound and doesn't have splices, which can lead to unwanted vibration.



#### **MFS™ Max Flange Shield**

The rubber guard extends beyond the rim and wraps around the lower sidewall of the tire to protect rims from accidental curb damage.

SIZE	SERVICE DESC.	LOAD RANGE	SIDE-WALL	PRODUCT CODE	MATERIAL NUMBER	RIM WIDTH (IN)	APPRVD. RIM WIDTHS (IN)	SECTION WIDTH (IN)	OVERALL DIAMETER (IN)	STATIC LOADED RADIUS (IN)	REVS/MILE	TREAD WIDTH (IN)	TREAD DEPTH (IN)	MAX. LOAD (LBS)	TIRE WEIGHT (LBS)	OE FITMENT
225/55ZR16	95Y	SL	BSW	265023757	193180	7.0	6.0 - 8.0	9.2	25.7	11.8	809	7.9	10/32	1521	24.0	
215/55ZR16	93Y	SL	BSW	265023756	193179	7.0	6.0 - 7.5	8.9	25.3	11.6	823	7.6	10/32	1433	24.0	
205/55ZR16	91Y	SL	BSW	265023755	193178	6.5	5.5 - 7.5	8.4	24.9	11.4	836	7.2	10/32	1356	24.0	
205/50ZR17	93Y	SL	BSW	265023750	193212	6.5	5.5 - 7.5	8.4	25.1	11.6	826	7.2	10/32	1433	24.0	
235/45ZR17	94Y	SL	BSW	265023747	193217	8.0	7.5 - 9.0	9.3	25.4	11.8	816	8.5	10/32	1477	24.0	AUDI A4 05
225/45ZR17	94Y	XL	BSW	265023746	193216	7.5	7.0 - 8.5	8.9	25.0	11.6	827	8.1	10/32	1477	24.0	
215/45ZR17	91Y	XL	BSW	265023745	193214	7.0	7.0 - 8.0	8.4	24.6	11.5	839	7.6	10/32	1356	24.0	
245/40ZR17	91Y	SL	BSW	265023741	193218	8.5	8.0 - 9.5	9.8	24.7	11.6	834	8.8	10/32	1356	24.0	
215/40ZR17	87Y	XL	BSW	265023740	193213	7.5	7.0 - 8.5	8.6	23.8	11.2	866	7.2	10/32	1201	24.0	
205/40ZR17	84W	XL	BSW	265023840	193211	7.5	7.0 - 8.0	8.3	23.5	11.1	876	7.2	10/32	1102	24.0	
245/45ZR18	100Y	XL	BSW	265023748	193224	8.0	7.5 - 9.0	9.6	26.7	12.4	775	8.5	10/32	1764	24.0	
235/40ZR18	95Y	XL	BSW	265023743	193221	8.5	8.0 - 9.5	9.5	25.4	12.0	810	8.5	10/32	1521	24.0	
225/40ZR18	92Y	XL	BSW	265023742	193220	8.0	7.5 - 9.0	9.1	25.1	11.8	820	8.1	10/32	1389	24.0	
265/35ZR18	97Y	XL	BSW	265023736	193227	9.5	9.0 - 10.5	10.7	25.3	12.0	812	9.6	10/32	1609	24.0	
255/35ZR18	94Y	XL	BSW	265023735	193226	9.0	8.5 - 10.0	10.2	25.0	11.8	821	9.1	10/32	1477	24.0	
245/35ZR18		XL	BSW	265023935	193222	8.5	8.0 - 9.5	9.8	24.8	11.7	829	8.8	10/32	1389	24.0	
245/40ZR19	98Y	XL	BSW	265023744	193231	8.5	8.0 - 9.5	9.8	26.7	12.6	771	8.5	10/32	1653	24.0	
275/35ZR19	100Y	XL	BSW	265023738	193234	9.5	9.0 - 11.0	10.9	26.6	12.6	773	9.1	10/32	1764	24.0	
235/35ZR19		XL	BSW	265023936	193230	8.5	8.0 - 9.5	9.5	25.5	12.1	805	8.5	10/32	1359	24.0	
225/35ZR19	88Y	XL	BSW	265023737	193229	8.0	7.5 - 9.0	9.1	25.2	12.0	813	8.1	10/32	1235	24.0	
275/30ZR19	96Y	XL	BSW	265023731	193233	9.5	9.0 - 10.0	10.9	25.6	12.2	803	9.6	10/32	1565	24.0	
255/30ZR19	91Y	XL	BSW	265023730	193232	9.0	8.5 - 9.5	10.2	25.1	12.0	818	9.3	10/32	1356	24.0	
275/35ZR20	102Y	XL	BSW	265023739	196519	9.5	9.0 - 11.0	10.9	27.6	12.7	747	9.1	10/32	1874	24.0	AUDI A8 05
245/35ZR20		XL	BSW	265023937	193235	8.5	8.0 - 9.5	9.8	26.8	12.7	766	8.8	10/32	1521	24.0	
285/30ZR20	99Y	XL	BSW	265023732	193236	10.0	9.5 - 10.5	11.4	26.8	12.8	766	10.5	10/32	1709	24.0	
265/35ZR22		XL	BSW	265023938	193237	9.5	9.0 - 10.5	10.7	29.3	14.0	699	9.4	10/32	1709	24.0	
305/30ZR22		XL	BSW	265023930	193238	11.0	11.0 - 12.0	12.3	29.3	14.0	701	10.9	10/32	1609	24.0	

UTQG: 240 AA A

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels.



DRIVERS KNOW.®