

SPORT PERFORMANCE**DUNLOP SP SPORT 01™ &
SP SPORT 01™ DSST**ULTRA QUIET
HIGH-PERFORMANCE TIRE

FEATURES	BENEFITS
• Jointless Band Technology JLB™	• Dependable ride uniformity and tread wear
• Aramid® reinforced bead	• Ensures tight and secure fit of the tire on the rim
• Max Flange Shield MFS™	• Protects rims from accidental curb damage
• Silica tread	• Increases dry and wet traction as well as reduces rolling resistance
• Dunlop Self-Supporting Technology (DSST) features a patented sidewall construction and specially-developed compounds**	• Continued mobility up to a distance of 50 miles at a maximum speed of 50 mph in normal conditions**

**Only on the SP Sport 01 DSST.

UNIQUE DUNLOP TECHNOLOGIES**JLB™ Jointless Band Technology**

It maintains the tire's ideal shape at highway speeds. Nylon is positioned in all the right places to improve handling and tread wear. And unlike sheet cap plies, this one is spiral wound and doesn't have splices, which can lead to unwanted vibration.

MFS™ Max Flange Shield

The rubber guard extends beyond the rim and wraps around the lower sidewall of the tire to protect rims from accidental curb damage.

SIZE	SERVICE DESC.	LOAD RANGE	SIDE-WALL	PRODUCT CODE	MATERIAL NUMBER	RIM WIDTH (IN)	APPRVD. RIM WIDTHS (IN)	SECTION WIDTH (IN)	OVERALL DIAMETER (IN)	STATIC LOADED RADIUS (IN)	REVS/MILE	TREAD WIDTH (IN)	TREAD DEPTH (IN)	MAX. LOAD (LBS)	TIRE WEIGHT (LBS)	OE FITMENT
SP SPORT 01																
205/65R15	94V	SL	BSW	265022395	189351	6.0	5.5 - 7.5	8.2	25.5	11.4	823	6.3	10/32	1477	21.4	
195/65R15	91V	SL	BSW	265022375	189337	6.0	5.5 - 7.0	7.9	25.0	11.2	839	6.0	10/32	1356	19.6	
205/60R15	91V	SL	BSW	265022390	189342	6.0	5.5 - 7.5	8.2	24.7	11.2	847	6.5	10/32	1356	19.8	
195/60R15	88V	SL	BSW	265022370	189335	6.0	5.5 - 7.0	7.9	24.2	11.1	862	6.2	10/32	1234	19.8	
225/60R16	98V	SL	BSW	265022330	189371	6.5	6.0 - 8.0	9.0	26.6	12.0	785	6.9	10/32	1653	25.1	
225/60R16	98W	SL	BSW	265022410	189370	6.5	6.0 - 8.0	9.0	26.6	12.0	785	7.0	10/32	1653	25.1	
225/55R16	95W	SL	BSW	265022405	189363	7.0	6.0 - 8.0	9.2	25.7	11.8	809	7.9	10/32	1521	24.5	
215/55R16	97V	XL	BSW	265022356	193047	7.0	6.0 - 7.5	8.9	25.3	11.6	823	7.6	10/32	1609	24.5	
205/55R16	91W	SL	BSW	265022455	189357	6.5	5.5 - 7.5	8.4	24.9	11.4	836	7.2	10/32	1356	20.5	
235/50R18	97V	SL	BSW	265023350	191212	7.5	6.5 - 8.5	9.6	27.3	12.6	761	8.2	10/32	1609	27.8	BMW X3 04
255/45R18	99V	SL	BSW	265023345	191213	8.5	8.0 - 9.5	10.0	27.0	12.6	765	8.6	10/32	1708	28.2	BMW X3 04
SP SPORT 01 DSST																
225/50R17	94W	SL	BSW	265023250	190492	7.0	6.0 - 8.0	9.2	25.9	12.0	802	7.9	10/32	1477	31.5	BMW 5 SERIES 04
245/45R17	95W	SL	BSW	265023245	190494	8.0	7.5 - 9.0	9.6	25.7	11.9	806	8.8	10/32	1521	30.5	BMW 5 SERIES 04
245/45R18	96W	SL	BSW	265023200	190496	8.0	7.5 - 9.0	9.6	26.7	12.4	775	8.8	10/32	1565	31.8	BMW 6 SERIES 04
275/40R18	99W	SL	BSW	265023240	190498	9.5	9.0 - 11.0	10.9	26.7	12.5	774	9.9	10/32	1708	26.5	BMW 6 SERIES 04
245/40R18	93W	SL	BSW	265023140	190488	8.5	8.0 - 9.5	9.8	25.7	12.1	801	8.8	10/32	1433	28.5	BMW 5 SERIES 04
245/40R18	93Y	SL	BSW	265023141	191759	8.5	8.0 - 9.5	9.8	25.7	12.1	804	9.6	10/32	1433	24.0	BMW 5 SERIES 04
205/40R18	82W	SL	BSW	265023241	193085	7.5	7.0 - 8.0	8.3	24.4	11.6	840	7.2	10/32	1047	21.6	BMW Mini Cooper S Works 04
275/35R18	95W	SL	BSW	265023136	191760	9.5	9.0 - 11.0	10.9	25.6	12.1	804	9.6	10/32	1521	30.4	BMW 5 SERIES 04
275/35R18	95Y	SL	BSW	265023135	190490	9.5	9.0 - 11.0	10.9	25.6	12.1	804	9.6	10/32	1521	30.4	BMW 5 SERIES 04
245/40R19	94W	SL	BSW	265023205	190500	8.5	8.0 - 9.5	9.8	26.7	12.6	771	8.8	10/32	1477	23.5	BMW 6 SERIES 04
275/35R19	96W	SL	BSW	265023210	190502	9.5	9.0 - 11.0	10.9	26.6	12.6	773	9.6	10/32	1565	23.5	BMW 6 SERIES 04

UTQG: 280 A A

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels.



DRIVERS KNOW.®